



SOLIKAMSKBUMPROM

# Technical Data Sheet SUPER LIGHT INTERLINER

The best interliner paper for cost-efficient corrugated board

100% fresh wood fibre

*In harmony with nature*

Parameter	Unit	Value			
		55	60	65	70
<b>BASIC CHARACTERISTICS</b>					
Basis weight (Grammage)	g/m <sup>2</sup>	55.0±2.0	60.0±2.0	65.0±2.0	70.0±2.0
Moisture content	%	8.0±2.0			
<b>STRUCTURAL CHARACTERISTICS</b>					
Bulk	cm <sup>3</sup> /g	1.8-2.0			
Thickness	µm	100±4	110±4	115±4	125±4
<b>OPTICAL CHARACTERISTICS</b>					
Shade (CIE) brown	L	non-dimensional	70 ± 4.0		
	a		3.0±1.0		
	b		14.0±1.0		
Shade (CIE) yellow-brown	L	non-dimensional	70±4.0		
	a		4.0±1.0		
	b		22.0±1.0		
<b>MECHANICAL CHARACTERISTICS</b>					
Tensile Strength	machine direction	kN/m	min 2.7		
Bursting Strength		kPa	min 90		
<b>OTHER CHARACTERISTICS</b>					
Reel Diameter		mm	900-1250		
Reel Diameter Tolerance		mm	+20/-50		
Reel Width		mm	350-2800		
Reel Width Tolerance		mm	±2		
Mill Join Per Reel		piece	max 2		
Core		MM	76/100		
Wrapping			Strong Kraft Paper Strong Moisture proof polyethylene laminated Kraft paper		

### Super lightweight paper 55-70 GSM

Perfect paper with strong mechanical properties  
For medium layers of multilayer containerboard, converting and packaging  
100% biodegradable  
100% compostable  
100% recyclable

