



SOLIKAMSKBUMPROM

Technical Data Sheet

NEWSPRINT WITH INCREASED BULKINESS

100% fresh wood fibre

In harmony with nature

Parameter	Unit	Value	
		55	
BASIC CHARACTERISTICS			
Basis weight (Grammage)	g/m ²	55.0±1.5	
Moisture content	%	8.0±2.0	
Ash content	%	1.5	
STRUCTURAL CHARACTERISTICS			
Bulkiness	cm ³ /g	min 1.8	
Thickness	µm	100±5	
Roughness (PPS)	µm	3.8±0.2	
OPTICAL CHARACTERISTICS			
Brightness	%	59.0±1.0	
Opacity	%	96.0±1.0	
Dominant wavelength	nm	572.0±1.0	
Shade (CIE)	L	non-dimensional	82.5
	a		-0.9
	b		2.5
	ΔE		max 0.7
MECHANICAL CHARACTERISTICS			
Tensile Index	machine direction	N m/g	min 45.0
Elongation	machine direction	%	1.0±0.1
OTHER CHARACTERISTICS			
Reel Diameter	mm	900-1250	
Reel Diameter Tolerance	mm	-20	
Reel Width	mm	270-2500	
Reel Width Tolerance	mm	±1	
Mill Join Per Reel	max	1	
Core	mm	76	
Wrapping		Strong Kraft Paper	

Newsprint with increased bulkiness 55 g/m²

For high-speed printing machines

Perfect paper with strong mechanical properties

100% biodegradable

100% compostable

100% recyclable



ISO 9001:2015
ISO 14001:2015



НАЦИОНАЛЬНАЯ СИСТЕМА
ЛЕСНОЙ СЕРТИФИКАЦИИ